

# Q35E Product Specification V 1.5

2013-11-05

	Detail	Descriptions
<b>Standard Equipments</b>	Operating System	Windows Embedded Handheld 6.5 Pro.
	Processor	T.I. Cortex A8 DM3730 @ 1GHz
	DRAM	512 MB
	Flash	4.5 GB
	Dispaly	QVGA 3.5" TFT Panel , Sunlight Readable
	Touch Panel	Resistive Touch Panel
	Camera	5M Pixels, Auto Focus
	Wireless Modules	Wi-Fi 802.11 b/g/n , Bluetooth 3.0
	GPSModule	Sirf IV
	UHF-RFID Module	Main Chip: Impinji R1000
	Audio	Build-In Speaker x 1 / Microphone x 1
	Key Pad	27 Keys ( Including Power Key )
	LED Indicators	AC-In / Charging Status Indicators
	IO Ports	6pin POGO Connector ( Support DC-IN & USB Client )
		Micro SD x 1 ( Up to 32GB )
	Li-Ion Battery Pack	Rechargeable, 2600mAh 3.7V x 2 cells
	Adaptor	90~265V , 47~63Hz Input , 19V/2A Output
	Dimension	176 mm(L) x 83 mm(W) x 43 mm(D)
	Weight	550g ( Including Battery Pack )
	Environment Specifications	Operating Temp. : -20°C~55°C ( Exclude Camera )
		Storage Temp. : -30°C~70°C
		Operating Humidity : 5%~95% none condensing
Industrial Grade	IP65 , 4 Feet Drop to Concrete	
Accessories	DC-In & USB Cable	
Certifications	FCC , CCC	
<b>Optional</b>	Data Comm.	WCDMA / EVDO
	Battery Pack	2600mAh 3.7V x 3cells / 3000mAh 3.7V x 3cells
	UHF-RFID Module	Main Chip : Impinji R500 / R2000
	Flash	16.5 GB
	Dispaly / Camera	VGA 3.5" TFT LCD , Sunlight Readable / 8MP , AF

## Q35E Product Photo :

- 7547U
- 7545U
- Black
- Red 032U
- Yellow U

